

STABLE

Quality Air Solution



COMPLETE SET
7.5HP – 20HP



ISO9001, ISO14001, ISO18001 Certificat



Excellent Compressor Stage




We provide heavy-duty compressor stages equipped with 'SKF' bearing featuring high efficiency, low noise longer service life design 25,000 hrs.

Excellent Direct Driver




We provide Direct-Driven rigid Connection and automatic alignment between motor and screw

Excellent PLC Controller



We provide Digital PLC Controller heavy-duty, famous part, feature safe and longer service life

Excellent Ridgid Piping



We provide Ridgid Oil Piping inside the Compressor . No oil leak and longer service life

Excellent Stainless Evaporator



We provide Stainless Steel Evaporator for Air Dryer improved corrosion resistance

Excellent Air Treatment



We provide High Quality Air Treatment 1 micron and 0.1 micron accordance with ISO 8573.1 : 2001 E

TECHNICAL PARAMETERS TABLE

Model	Free Air Deliver m3/min	Discharge Pressure BAR	Noise dB(A)	Motor	Dimension			Weight KG	Air Outlet Pipe Diameter Inch	Rotor Speed rpm
				Power KW/HP	L mm	W mm	H mm			
CPA-7.5	0.79	8	62+2	5.5/7.5	1740	600	1500	350	3/4"	350
	0.69	10								
	0.63	13								
CPA-10	1.05	8	62+2	7.5/10	1740	600	1500	350	3/4"	350
	0.92	10								
	0.84	13								
CPA-15	1.61	8	63+2	11/15	1750	700	1780	485	3/4"	500
	1.41	10								
	1.29	13								
CPA-20	2.13	8	63+2	15/20	1750	700	1780	485	3/4"	500
	1.87	10								
	1.71	13								
CP-7.5	0.79/0.69	8/10	62+2	5.5/7.5	1400	600	1480	290	3/4"	260
CP-10	1.05/0.92	8/10	62+2	7.5/10	1400	600	1480	300	3/4"	260
CP-15	1.61/1.41	8/10	63+2	11/15	1540	700	1640	340	3/4"	300
CP-20	2.13/1.87	8/10	63+2	15/20	1540	700	1640	350	3/4"	300

Due to improvement for excellence, the specification subject to change without notice in advance Free air delivery standard in GB/T3853-eqr-ISO 1217